



logiJET T6-2

**MAXIMUM
FLEXIBILITY FOR
SMOOTH PRODUCTION
AND LOGISTICS
PROCESSES**

PCL5 Compatible 6-Inch Thermal Printer

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Compatible with: PCL5, IGP, IPDS, PDF, ZPL II, and many more.
- WIFI optional
- Laser printer compatible
- SAP® and AS/400 compatible (through PCL5 + JetCAPS as well as LAN-IPDS)
- Process integration with optional GPIO interface
- RFID optional

FIELDS OF APPLICATION

- Stickers, labels and tags
- RFID tags
- Just-in-time printing or batch processing
- Logistics, commissioning, production, shipping, etc.



Print Engine

Print technology	Thermal transfer/direct thermal harmonic (history-controlled flat head technology)
Controller	MPC 8.x
Print speed	up to 6 Inch/s up to 150 mm/s
Print resolution	300 dpi x 300 dpi
Lifetime print head	Transfer: up to 50.000 m, Direct: up to 25.000m
Power supply	110/240VAC, 50/60Hz
Power consumption	3.3 A
Dimensions (WxDxH)	13,6" [345 mm] x 20,3" [516mm] x 11,2" [285 mm]
Weight	37.5 lbs [17 kg] (without options)
Environment temperature	5 - 40°C
Relative humidity	30 - 85 % (rel., non-condensing)
Interfaces	USB Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP)
Optional*	IEEE 1284 (Centronics), RS232, RS422 WiFi: IEEE 802.11 n/g/b, WEP with 64 and 128 Bit, WPA/WPA2, WPA-PSK/WPA2-PSK
Memory	RAM: 256 MB, Flash: 256 MB

MPC 8.x High-End Print-Controller

Emulations

MICROPLEX IDOL, AGFA Reno, LN03+, BULL-MP6090, IGP/PGL, Datamax, Etimark MP-1220, TEC Bx72, TEC B6xx, LDC, ZPL II, EPL2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, Diablo 630, IBM Proprinter, Epson FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, HP Designjet, XML (SAP® RFID), CUPS Raster

Optional Emulations

HP-PCL5/ HPGL, µ-Postscript, CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, Labelpoint, IPDS, AEA, PDF Direct Printing** (more emulations on request)

Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Additional functions

Network capabilities authentication standard IEEE 802.1X

Intelligent barcode generation on-the-fly in the printer

Format splitting in several subformats by command

Optional functions

Integrated form management (RFM)

Forms and fonts can be stored in the flash memory and can be accessed when needed.

Status-Out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC.


Integration of the printer into production lines is possible, controlled by GPIO-interface

Customer / Application specific modifications possible.



Printable Media

Size	
Width	max. 7" [178 mm] [6.6" [165 mm] withCutter] printable width 6.61" [168 mm]
roll diameter	max. 8" [203 mm]
core diameter	1,5" - 3" [38.1 - 76.2 mm]
Paper thickness	0.0024" - 0.01" [0.06 - 0.25 mm]
Thermal transfer ribbon	
roll diameter	max. 3" [76 mm]
Core diameter	1" [25.4 mm]
Ribbon length	max. 450 m
Coated side	inside or outside
Ribbon width	2.36" - 6.85" [60 - 174 mm]



Paper Path

Input	
Continuous	internal: from roll external: e.g. fanfold
	sensor for black mark and label gap (reflection and transmissive)
Output	
Single/Job	tear-off
Optional	
Continuous	internal Peeler / Rewinder
Single	peel-off, Cutter
Job	cutter
Option RFID	
Frequency Range	865.600 - 867.600 MHz (ETSI EN 302 208 v 3.1.1)
RF Power	programmable in 18 levels (1 dB step) from 10 dBm to 27 dBm (from 10 mW to 500 mW) conducted
Standard Protocols	EPC C1 G2 / ISO18000-63
Features	read/write/verify (void)
Registration of antenna position	automatic (depending on antenna design)

* Not all interface options can be activated at the same time.
** Only available with MPC 3.4, MPC 3.6, MPC 7.1 and MPC 8.x

EMEA
APAC

MICROPLEX PRINTWARE AG
Panzerstraße 5, 26316 Varel
Germany
Phone: +49 4451 91370
E-Mail: sales@microplex.de

AMER
Canada

MICROPLEX PRINTWARE CORPORATION
30300 Solon Industrial Pkwy Suite E, Solon, OH 44139
USA
Phone: +1 440-374-2424
E-Mail: info@microplex-usa.com

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 19.04.2023

