



SOLID 60A3

PERFORMANCE FOR LOGISTICS, AUTOMOTIVE AND PRODUCTION

A3 laser Printer for Just-in-Time Applications

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Full integration in production lines through GPIO and Status-Out
- > First page after 3 seconds
- Paper refill to 2x1,000 sheet feeder during operation
- Flexible extension options for paper feed and tray
- Duplex printing as standard
- Optional IPDS emulation making it the printer of choice for IBM® solutions
- Face-up option

FIELD OF APPLICATION

- Just-in-time Applications
- On-Demand printing
- Business and workflow documents





Print Engine

Print technology Laser, OPC

heat / pressure

Controller MPC 7.1

 Print speed
 up to 60 pages/minute (A4)

 Print resolution
 max. 600 dpi x 600 dpi

 Duty cycle
 up to 53,000 pages (A4)

(based on a using period of 60 months)

max. 300,000 pages (A4)

 Power supply
 220-240 VAC, 50 Hz

 Power consumption
 max. 1.780 W

Dimensions (WxDxH)587 x 653 x 720 (printer only)Weight57 kg (without options)

Relative humidity 15 - 80 % (rel., non condensing)

Environment temperature 10 - 32°C **Interfaces** USB

Ethernet-Interface, 10/100/1000 Mb/s, bi-directional (TCP/IP)

Option WiFi IEEE 802.11 n/g/b, WEP with 64 and 128 Bit,

WPA/WPA2, WPA-PSK/WPA2-PSK
IEEE 1284 (Centronics) **OR** RS232, RS422

Memory RAM: 1024 MB

Flash: 32 GB

MPC 7.1 High-End Print-Controller



MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, μ -Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, XML (SAP® RFID), CUPS Raster

Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL, cab, Datamax, Labelpoint, LDC, ZPL II, EPL 2, Intermec Direct Protocol, IER Command, Godex EZPL, HP Designjet, IPDS, AEA, PDF Direct Printing*, (more emulations on request)

Barcodes

Codabar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Strich Datalogic), Interleaved 2/5 (3-Strich Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Additional functions

Network capabilities authentication standard IEEE 802.1X

Intelligent barcode generation on-the-fly in the printer

Format splitting in several subformats by command

Integrated form management (RFM) Forms and fonts can be stored in the flash memory

and can be accessed when needed

Optional functions

Status-Out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC. Integration of the printer into production lines is possible, controlled by GPIO-interface Customer / Application specific modifications possible.

* Only available from MPC 3.4, MPC 3.6, MPC 7.x and MPC 8.x

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 11.04.2024

MICROPLEX PRINTWARE AG

Panzerstraße 5, 26316 Varel

German

Phone: +49 4451 91370 E-Mail: sales@microplex.de

VMED

AMER Canada

MICROPLEX PRINTWARE CORPORATION

30300 Solon Industrial Pkwy Suite E, Solon, OH 44139

Phone: +1 440-374-2424 E-Mail: info@microplex-usa.com

PRINTING TECHNOLOGIES


SPECIFICATIONS



Printable Media

 Size
 A6 - A3

 Weight
 60 to 300 g/m² Duplex max. 256 g/m²



Paper Input / Output

Input

Feeder 1+2: 550 sheet (A6 .. A3) Manual Feeder: 100 sheet (A6 .. A3)

Optional

Feeder 3+4:550 sheet each (A6 to A3) or Large capacity feeder with 1,000 + 1,000 sheet A4

Output

face down

Optional

face up (max. 169 g/m²) (Factory option) Signal system

Lifetime Consumables

Toner: 42,000 pages A4 (5% coverage)*
OPC: 160,000 pages A4*

*: depending on the number of pages per print job