

MICROPLEX SOLID F44

Continuous Form Laser Printer

The **SOLID F44** is a versatile, easy-to-use, continuous form, monochrome Laser printer.


The **F44** printer offers a small footprint and provides the user with versatile and reliable media management capabilities, by utilizing the pin-fed tractor assembly and the (iPS), intelligent Paper Stacker.

Handling media widths of up to 12 inches wide, the **F44** is perfectly suited for decentralized, network-based environments, supporting industries and print applications such as **oil and gas for Well Logs, USPS required IMB (Intelligent Mail Barcode), for 1-up Address Labels, banking, insurance, fulfillment services, health services, distribution and logistics.**



HIGHLIGHTS

- Print Speed: **44 pages per minute** (Letter, Landscape)
34 pages per minute (Letter format, 11" length)
- Monthly duty cycle: **50,000 pages/month** (Letter format)
- 600 x 600 dots/inch print resolution
- Compact design to fit in limited floor space
- Accurate media stacking, up to 2,000 pages, no Operator involvement
- Up to 12" wide media, 11" wide print width
- User-friendly, easy set-up, easy to operate
- Tear-off edge for separating of printed form sets
- **Replacement product for aging, end-of-life, SOLID F24, SOLID F32 or comparable printers!!**



MICROPLEX®

Toll Free: 877.997.6543
www.MICROPLEX-USA.com

MICROPLEX SOLID F44

Continuous Form Laser Printer

SPECIFICATIONS

Print Speed: 34 pages / minute (Letter page is 11" long)
44 pages / minute (rotated, landscape Letter is 8.5" long)
2.267 lines / minute at 6 lines / inch

Resolution: 600 x 600 dpi

Workload: 50,000 pages per month (Letter, landscape)

Print Method:

Electro photographic, single Laser Diode, OrganicPhoto Conductor (OPC), 1, single component toner/developer, heat and pressure fuser roller system with adjustable fusing temperature

Control Panel: Two line LCD display (16 characters/line)

Function Keys: ONLINE, FORMFEED, MENU, CANCEL

Dimensions, Printer: 21.2" (539 mm) x 19.6" (498 mm) x 23.1 (780 mm)
(W x H x D) (inclusive tractor cassettes)

Weight: 88.2 lbs. (40 kg) incl. imaging cartridge

Rated Voltage / Maximum current:

100-110 V AC, 50 - 60 Hz / 15 Amps

110-120 V AC, 50 - 60 Hz / 12.5 Amps

220-240 V AC, 50 - 60 Hz / 6.5 Amps

Power Consumption:

Operating < 800 W average (< 1,300 W max)

Stand-by < 110 W average (< 1,200 W max)

Sleep < 45 W average

Environmental Conditions:

Operating: +10 to + 35°C, 15 to 85% relative humidity

Storage (Printer & Supplies): 0 to + 35°C, 30 - 85 % rel.hum.

Sound Level: < 60 dB(A) operating

Engine Lifetime: 2,000,000 pages

Agency Approvals: VDE/GS, UL, C-UL, CE, FCC,GOST-R

CONTROL UNIT

Processor: Power PC

Data Memory: 128 MB, Standard

Program & Font Memory: 32 MB Flash EPROM, onsite software updates

Stacker Control: Supports attached iPS , F44

MEDIA HANDLING

Type: Continuous forms / media with tractor pin holes

Paper Transport: Tractor-feed Assembly, Transport belts

Paper Input: from front with use of Tractor-feed Assembly

Paper Output: out top, directed to the rear with media guide

MEDIA CAPABILITIES

Media Width: min. 4 inch, max. 12 inch (print area, 11 inch)

Media Length: F44 Printer w. iPS F44 min. 7 inch, max. 17 inch
F44 Printer, only min.3 inch, max. 20 inch

Media Weight: 64 g/m² up to 157 g/m²

CONSUMABLES

Imaging Cartridge (includes toner, developer, OPC drum): 18,000 pages (estimate for Letter format, 5% toner coverage)

CONNECTIVITY

INTERFACES, EMULATIONS, BARCODES

Interfaces: 10BaseT/1 Ethernet, 00BaseTX, Parallel IEEE 1284 and USB 2.0 (in development)

Emulations / PDL: HP LaserJet 4 (PCL 5e, PJJ), HP - GL/2, PCL/PJL Extensions (Optional data stream Converter available for IPDS.)

Fonts: 45 scalable fonts, 10 bitmap fonts

Barcodes: USPS IMB and Postnet, Code 39, Code 93, Code 128, Codabar, 2/5 industrial, 2/5 interleaved, EAN 8/13 Add on 2/5, MSI, UPC-A, UPC-E, KIX-Code, Datamatrix Code

OPTIONS

iPS (intelligent Paper Stacker) F44: Assures accurate stacking of forms up to 2,000 pages, without operator involvement

Dimensions:

iPS F44: 19.9" (506mm) x 28.3 (720mm) x 43.8" (1,113mm) (W x H x D)

F44 Printer with iPS F44: 21.2" (540) x 47.6" (1,208) x 44.0" (1,118 mm) (W x H x D)

Weight: iPS F44: 94.8 lbs (43 kg) F44 Printer and iPS F44: 183 lbs (83 kg)

Printer Drivers: Windows 3.x/95/98/NT/2000/XP/7, and Linux.

Printer Configuration Software (Windows 95/98/NT, 2000/XP/7 and Linux) Profiler, Profile Selector and SAP R/3 device types, are available upon request.

Product names mentioned here in are trademarks and/or registered trademarks of their respective companies.

All written numbers and specifications in this data sheet are for description purposes only. No promise or guarantee is made as to the accuracy of the numbers or specification provided and furthermore no guarantee is provided that the numbers quoted or specification given will be that of the final product purchased. It remains the duty of the buyer to confirm and prove that the specification provided in the product meets with the buyers needs regarding the buyers specific application and/or installation. Technical specifications may be changed at any time without notice.

MICROPLEX Printware Corporation · 100 Northfield Road · Bedford, OH 44146

Phone: 440.374.2424 · Fax: 440.374.2422 · Toll Free: 877.99SOLID · info@MICROPLEX-USA.com



MICROPLEX®

Toll Free: 877.997.6543
www.MICROPLEX-USA.com