

## Replacement Solutions for Printronix® L5020 and L5535 Continuous Laser Printers.

Printronix has withdrawn the L5535 from the market, after a lengthy and successful run, because it can no longer be produced economically for the worldwide customer base.”

If you currently own one of the Printronix L5XXX series, continuous form laser printers and are experiencing increasing support costs and downtime, you now have a fantastic replacement path with solutions from MICROPLEX. (1:1 Replacement).



MICROPLEX’s continuous forms laser printers have been “the printers of choice” for replacing the aging installed base of the Printronix L5XXX product line. The SOLID 60E-2, SOLID 84E and SOLID 166E are offering all of the print technologies that were developed into the L5XXX series products and also offers increased speeds, improved print quality, lower cost-of-ownership, smaller footprint (SOLID 60E-2), ease-of-use for Operators; all at a price-point below your original product purchase.



Product features	SOLID 60E-2	SOLID 85E	SOLID 166E	Printronix® L5020 (end-of-life)	Printronix® L5535 (end-of-life)
Print speed	60 ppm (A4 Landscape)	85 ppm (A4 2-up)	166 ppm (A4 2-up)	20 ppm (A4 Landscape)	35 ppm (A4 Landscape)
Media Handling	Power Stacker (Standard, no extra charge )	Power Stacker (Standard, no extra charge )	Power Stacker (Standard, no extra charge )	Power Stacker (optional)	Power Stacker (optional)
Recommended monthly	300.000	750.000	850.000	200.000	300.000
Emulations	VGL/PGL, IGP, Tally MT6xx, IBM Proprinter, Epson FX, PCL5e, MPX IDOL and much more	VGL/PGL, IGP, Tally MT6xx, IBM Proprinter, Epson FX, PCL5e, MPX IDOL and much more	VGL/PGL, IGP, Tally MT6xx, IBM Proprinter, Epson FX, PCL5e, MPX IDOL und and much more	PTX LinePrinter Plus PCL5e, VGL, PGL	PTX LinePrinter Plus PCL5e, VGL, PGL
Connectivity	Parallel, USB, Ethernet	Parallel, USB, Ethernet	Parallel, USB, Ethernet	Parallel, seriell Ethernet optional	Parallel, seriell Ethernet optional
Memory	1024MB	1024 MB	1024 MB	32 MB	32 MB
Controller Clock Speed	>3 GHz	>3 GHz	>3 GHz	66 MHz	66 MHz
Firmware Updates	Free Updates (Life of printer)	Free Updates (Life of printer)	Free Updates (Life of printer)	Not supported	Not supported
Resolution (DPI)	300x300 600x600	300x300 600x600	300x300 600x600	300x300 400x400 optional	300x300 400x400 optional
Dimensions (BxTxH)in Inch	31,7“x33,5“x49,2“	30,7“x36,8“x52“	62,2“x34,3“x53,2“	30“x50,4“x48“	50,6“x36,9“x47,5“
Weight (pounds)	529,1	661,4	1124,4	352,8	507,1