∢ microplex

ENJOY THE PERFORMANCE AND EASY HANDLING

SOLID 120A3-2



A3 Laser Printer for Just-in-Time Applications

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Minimal downtime and extremely long maintenance intervals
- > Toner refill possible during operation
- > Extremely fast printing speed
- Flexible expansion options for paper feed and tray
- Duplex printing at full printing speed
- Optional IPDS emulation making it the printer of choice for IBM® solutions

FIELD OF APPLICATION

- > Just-in-time applications
- On-demand printing
- > Business and workflow documents



SOLID 120A3



Print Engine

Print technology

Controller Print speed

Print resolution Duty cycle

Power supply Power consumption Dimensions (WxDxH)

Weight Environment temperature Relative humidity Interfaces

MPC 3.6 High-End Print-Controller

TIFF, XML (SAP® RFID), CUPS Raster,

Printing*, (more emulations on request)

Optional Barcodes (Barcode 2)

Intelligent barcode generation

Integrated form management (RFM)

Additional functions

Format splitting

Optional functions

Status-out

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, µ-Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom,

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL, Datamax, Labelpoint, LDC, ZPLII, EPL 2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, HP Designjet, IPDS, AEA, PDF Direct

Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

on-the-fly in the printer

gives notice of each correctly printed page via interface. Further features can be found in the manual.

EMBEDDED INTELLIGENCE - Enabling two-way communication between printer and a PLC.

Integration of the printer into production lines is possible, controlled by GPIO-interface

in several subformats by command

and can be accessed when needed

Forms and fonts can be stored in the flash memory

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic),

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Memory

Emulations

Barcodes

Optional Emulations

Laser, OPC heat / pressure MPC 3.6 up to 120 pages/minute (A4) up to 54 pages/minute (A3) max. 600 dpi x 600 dpi up to 400,000 pages (A4 landscape) (based on a using period of 60 months) max. 500,000 pages (A4 landscape)) 220-240 VAC, 50 Hz 13 A 34.3" (870 mm) x 29.9" (760 mm) x 38.6" (980 mm) (printer only) 42.5" (1080 mm) x 31.9" (810 mm) x 46.9 (1190 mm) (incl. Display) approx. 661 lbs (ca. 300 kg) (without options) 10 - 30°C 20 - 85 % (rel., non condensing) USB IEEE 1284 (Centronics) Ethernet-Interface 10/100/1000 MBit, bi-directional (TCP/IP) RAM: 2 GB Flash: 50 MB






Printable Media

R* - A3W*
to 220 g/m ax. 300 g/m

60 to 220 g/m² max. 300 g/m² (option 3430 is required)



Paper Path

Input

cassette 1+2: 1,200 and 800 sheets (A4/Letter) cassette 3: 500 sheets (B5R* bis A3W**) cassette 4: 500 sheets (A5R* to A3W**)

Optional

up to 3,500 sheets A4, B5 (3433) up to 5,000 sheets (3430) (each 2,500 sheets in tray 5 and 6) A3W** - A5R* (no offset)

Output

face up / face down

Optional

finisher saddle stitching (3440) 4,000 sheets, 100-sheets-stitching A3 – B5R* (offset/stitching), A3W** – A5R* (no offset) (more options on request)

* R = short side feeding **A3W = 12" x 18" (304mm x 457mm)

* Only available with MPC 3.4, MPC 3.6, MPC 7.1 and MPC 8.x

Programmable GPIO-Interface (SPS-Control)

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 31.07.2023

Customer / Application specific modifications possible.

MICROPLEX PRINTWARE AG Panzerstraße 5, 26316 Varel Germany Phone: +49 4451 91370 E-Mail: sales@microplex.de

MICROPLEX PRINTWARE CORPORATION 30300 Solon Industrial Pkwy Suite E, Solon, OH 44139 USA Phone: +1 440-374-2424

E-Mail: info@microplex-usa.com