

SOLID 90A3-2

**HIGHEST
PERFORMANCE
FOR BUSINESS,
LOGISTICS
AND PRODUCTION**

A3 Laser Printer for Just-in-Time Applications

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Minimal downtime and extremely long maintenance intervals
- Toner refill possible during operation
- Extremely fast printing speed
- Flexible expansion options for paper feed and tray
- Duplex printing at full printing speed
- Optional IPDS emulation making it the printer of choice for IBM® solutions

FIELD OF APPLICATION

- Just-in-time applications
- On-demand printing
- Business and workflow documents



Print Engine

Print technology	Laser, OPC heat / pressure
Controller	MPC 3.6
Print speed	up to 90 pages/minute (A4) up to 47 pages/minute (A3)
Print resolution	max. 600 dpi x 600 dpi
Duty cycle	up to 400,000 pages (A4 landscape) (based on a using period of 60 months) max. 500,000 pages (A4 landscape)
Power supply	220-240 VAC, 50 Hz
Power consumption	3.55 KW (16 A)
Dimensions (WxDxH)	34.3" (870 mm) x 29.9" (760 mm) x 38.6" (980 mm) (printer only) 42.5" (1080 mm) x 31.9" (810 mm) x 46.9 (1190 mm) (incl. Display)
Weight	approx. 661 lbs (ca. 300 kg) (without options)
Environment temperature	10 - 30°C
Relative humidity	20 - 85 % (rel., non condensing)
Interfaces	USB IEEE 1284 (Centronics) Ethernet-Interface 10/100/1000 MBit, bi-directional (TCP/IP)
Memory	RAM: 2 GB Flash: 50 MB

MPC 3.6 High-End Print-Controller

Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, μ -Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, XML (SAP® RFID), CUPS Raster, RFM

Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL, Datamax, Labelpoint, LDC, ZPLII, EPL 2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, HP Designjet, IPDS, AEA, PDF Direct Printing* (more emulations on request)

Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes (Bacode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Additional functions

Intelligent barcode generation	on-the-fly in the printer
Format splitting	in several subformats by command
Integrated form management (RFM)	Forms and fonts can be stored in the flash memory and can be accessed when needed

Optional functions

Status-out

gives notice of each correctly printed page via interface. Further features can be found in the manual.


Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC.
Integration of the printer into production lines is possible, controlled by GPIO-interface
Customer / Application specific modifications possible.



Printable Media

Size	A5R* - A3W*
Weight	60 to 220 g/m ² max. 300 g/m ² (option 3430 is required)



Paper Path

Input

cassette 1+2: 1,200 and 800 sheets (A4/Letter)
cassette 3: 500 sheets (B5R* to A3W**)
cassette 4: 500 sheets (A5R* to A3W**)

Optional

up to 3,500 sheets A4, B5 (3433)
up to 3,000 sheets A3W** to B5 (3425)
up to 5,000 sheets A3W** to B5R (3430)
(each 2,500 sheets in bin 5 and 6)
A3W** - B5R* (no offset)

Output

face-up / face-down

Optional

finisher (Art. 3441)
3,250 sheets, 50-sheets-stitching
A3 - B5R (offset/stitching)
A3W** - A5R* (no offset).

finisher with saddle stitching (3440)
4,000 sheets, 100-sheets-stitching
A3 - B5R* (offset/stitching), A3W** - A5R
(no offset) (more options on request)

* R = short side feeding
**A3W = 12" x 18" (304mm x 457mm)

* Only available with MPC 3.4, MPC 3.6, MPC 7.1 and MPC 8.x

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 12.07.2022

EMEA
APAC

MICROPLEX PRINTWARE AG
Panzerstraße 5, 26316 Varel
Germany
Phone: +49 4451 91370
E-Mail: sales@microplex.de

AMER
Canada

MICROPLEX PRINTWARE CORPORATION
30300 Solon Industrial Pkwy Suite E, Solon, OH 44139
USA
Phone: +1 440-374-2424
E-Mail: info@microplex-usa.com

