



PRINTING TECHNOLOGIES
ENGINEERED IN GERMANY

Your Microplex Partner:

EMEA
APAC

MICROPLEX PRINTWARE AG
Panzerstraße 5, 26316 Varel
Phone: +49 4451 91370
E-Mail: sales@microplex.de
www.microplex.de

AMER
Canada

MICROPLEX PRINTWARE CORPORATION
30300 Solon Industrial Pkwy Suite E, Solon, OH 44139
Phone: +1 440-374-2424
E-Mail: info@microplex-usa.com
www.microplex-usa.com

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case.
Version 03.05.2022



Thermal Printer Family

**MAXIMUM FLEXIBILITY
FOR SMOOTH
PRODUCTION
WITH THERMAL PRINT
TECHNOLOGY**

FIELD OF APPLICATION

- Mobile applications
- Heavy duty printing applications
- Two-color applications
- UHF RFID option available

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Mobile use with 12 V, 24 V, 36 V or 48 V DC
- Compatible with: PCL5, PDF, IPDS, ZPL II and many more
- Format widths from 4 inches to 8 inches
- Fast, robust and reliable
- Compact design, optional mounting plate (logiJET TM4, TM8)
- Robust metal case

MAXIMUM FLEXIBILITY FOR SMOOTH PRODUCTION WITH THERMAL PRINT TECHNOLOGY



The Perfect Fit for any Application

Within the **Microplex Thermal Printer Family** you will find the best printer solution in terms of print width, speed, material handling and size for any application scenario.

Heavy-Duty Thermal Printer for the Toughest Continuous Loads



SOLID T4-2



SOLID T6



SOLID T8

- SOLID thermal printer for toughest demands in production 24/7
- Print speed up to 406 mm/s
- Material width from 1 inch up to 10 inch
- High resolution printout with 300 dpi

Robust Industrial Printers for Production and Logistics



logiJET T4-2



logiJET T6-2



logiJET T8-3

- Robust metal case, easy handling, versatile and reliable
- 300 dpi print resolution
- Up to 150 mm/s print speed
- „Just-in-Time“ printing for production and logistics

Mobile Thermal Printer



logiJET TM4



logiJET TM8



logiJET TC8

- Mobile and network-independent thermal printing
- Material width from 1 inch up to 8.7 inch
- 2-color thermal transfer printing
- BS5609 compatible

2-Color-Thermal

Print Module



PM-T8

Tractor-Thermal



SOLID 45ET-2

RFID



logiJET T4-2

- The PM-T8 can be flexibly used as a print module in plant construction.
- The SOLID 45ET-2 can be equipped with two different paper sizes.
- RFID option is available for logiJET T4-2, logiJET T6-2, logiJET TM8, PM-T8.

Multiple Configurations are Possible

Microplex printer with its Multi Intelligence Controller provides multiple configuration possibilities. Via configuration the printers can be adjusted to nearly any application requirement. More than **40 printer emulations** can be selected. Every emulation can be fine tuned. Beside software signals via **SNMP** and **Status-Out** also electrical signals can be used to control the printer and therefore establish a real handshake between printer and system.

- Monitoring and control of the print out via electrical signals with 8 input and 8 output channels (**GPIO / SPS-Control**)
- Monitoring the printer status via **SNMP** (fleet management)
- User friendly configuration via **web panel**
- Modern WLAN interface with all current protocols, security standards and authentication standards (**IEEE 802.1X**)

Emulations and Barcodes

Thermal Printer Emulations, i.e.

ZPL II, EPL2, IGP/PGL, Datamax, TEC, IER-Command, Intermec Direct Protocol, LDC, LabelPoint, Etimark MP-1220, cab

Matrix Printer Emulations, i.e.

IGP/VGL, IGP/PGL, Epson FX-80, Ansi Genicom, CODE-V, MT-600, IBM Proprinter, IPDS

Two-Width Codes

Codabar, Code39, MSI, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix)

Height-Modulated Codes

Postnet, Planet, KIX, Royalbar, USPS One Code

Laser Printer Emulations, i.e.

PCL5, IGP/PGL, XES, Kyocera Prescribe, Kodescript+, AGFA Reno, LN03+, BULL-MP6090

Further Emulations

PDF, CUPS-Raster, HPGL, TIFF, Diablo 630, Lineprinter

Multiple-Width Codes

EAN-8, EAN-13, EAN-128, Add-on-Codes, Code 11, Code93, Code 128, UPC-A, UPC-E

2D-Barcodes

Aztec-Code, PDF 417, Datamatrix, Maxi-Code, USD-5, QR-Code

Option RFID

Frequency Range RF Power

865.600-867.600 (ETSI EN 302 208)
programmable in 15 levels (1dB step) from 9dBm to 23dBm (from 8mW to 200mW) conducted

Standard Protocols

Features

Registration of Antenna Position


EPC C1 G2 / ISO18000-6C
read/write/verify (void)

manual, automatic (depending on antenna design)

Individual Firmware Adaptation

If a „standard“ Microplex printer does not meet the needed requirements to fit into one specific application or should there be any special requests, we are always able to customize our firmware and make the printer work within the application.

- Individual electrical signals (GPIO / SPS-Control)
- Hardware modifications of the printers
- Emulation adaptations to fully support the customers print data
- Adaptation of status messages (Status-Out)



Examples of the integration of mobile Microplex thermal printers in industrial environments.