



A4 Laser Printer for Just-in-Time Applications

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- ➤ WIFI and PDF direct printing optional
- Duplex printing standard
- > Flexible extension options for paper feed and tray
- Full integration in production lines through GPIO / Status-Out

FIELD OF APPLICATION

- Paper exit face-up and face-down
- ▶ Integration with GPIO bi-directional communication
- Special paper sizes like A6, small GTL (74 x 210 mm)
- Printing with different emulations (PCL5, IGP, IPDS, etc.)



Print Engine

Print technology Laser, OPC

heat / pressure

Controller MPC 7.1

Print speed up to 52 pages/minute (A4)

first page: approx. 5,9 s

 Print resolution
 max. 600 dpi x 600 dpi

 Duty cycle
 up to 50.000 pages [A4]

(based on a using period of 60 months)

max. 250.000 pages (A4)

 Power supply
 220-240 VAC, 50/60 Hz

 Power consumption
 700 W (Sleep Mode: 4,2 W)

Dimensions (WxDxH in mm) 428 x 511 x 442

Weight 26 kg (incl. consumables)

Noise < 57 dB (A) Environment temperature 10 - 32°C

Relative humidity 8 - 80 % (rel., non condensing)

Interfaces USB 2.0,

Ethernet-Interface, 10/100 MBit, bi-directional (TCP/IP)

Factory Option IEEE 1284 (Centronics)

Option RS232, RS422

WIFI: IEEE 802.11 n/g/b, WEP with 64 and 128 Bit,

WPA/WPA2, WPA-PSK/WPA2-PSK

Memory RAM: 1024MB

Flash: 32 GB



MPC 7.1 High-End Print-Controller

Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, μ-Postscript, LN03+, BULL-MP6090, Datamax, Etimark MP-1220, TEC Bx72, TEC B6xx, LDC, ZPLII, EPL 2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, HP Designjet, XML (SAP® RFID), CUPS Raster

Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL, Labelpoint, IPDS, AEA, PDF Direct Printing*, (more emulations on request)

Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5, (more barcodes on request)

Additional functions

Network capabilities authentication standard IEEE 802.1X

Intelligent barcode generation on-the-fly in the printer

Format splitting in several subformats by command

Integrated form management (RFM) Forms and fonts can be stored in the flash memory

and can be accessed when needed

Optional functions

Status-Out

Gives notice of each correctly printed page via interface. Further features can be found in the manual.

Programmable GPIO-Interface (SPS-Control)

 ${\sf EMBEDDED\ INTELLIGENCE-Enabling\ two-way\ communication\ between\ printer\ and\ a\ PLC.}$

Integration of the printer into production lines is possible, controlled by GPIO-interface $\,$

Customer / Application specific modifications possible. Further features can be found in the manual.





Printable Media

Size A6 to A4, special formats on request

Weight 60 - 203 g/m²

Duplex 60 - 203 g/m²

Paper Path

Input (Standard)

Cassette 1: 550 sheets (Ax to A4) 75 g/m²

Output (Standard)

550 sheets (75 g/m 2)

Input (optional)

550 sheets (75 g/m²) tray 550 sheets (75 g/m²) lockable tray

up to 4 x 550 sheet trays usable

or 3 x 550 sheet trays

plus 1 x 2100 sheet tray (75 g/m²) Caster Base for 2100 sheet tray needed

Output (optional)

Output expander 500 sheets (75 g/m²) (upt to 3 times) Face-up-Option

Other options

Spacer (non fuctioning input tray to elevate the

printer)

Caster Base (only necessary for 2100 sheet

tray)

SOLID 52A4 MICR as extra model available.

* Only available with MPC 3.4, MPC 7.1 and MPC 8.x

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 22.08.2022

EMEA APAC MICROPLEX PRINTWARE AG Panzerstraße 5, 26316 Varel

Panzerstraße 5, 26316 Varel Germany

Phone: +49 4451 91370 E-Mail: sales@microplex.de AMER

MICROPLEX PRINTWARE CORPORATION

30300 Solon Industrial Pkwy Suite E, Solon, 0H 44139

USA

Phone: +1 440-374-2424 E-Mail: info@microplex-usa.com

