



A4 Laser Printer for Just-in-Time Applications

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- ➤ WIFI and PDF direct printing optional
- Duplex printing standard
- Flexible extension options for paper feed and tray
- Full integration in production lines through GPIO / Status-Out

FIELD OF APPLICATION

- Paper exit face-up and face-down
- ▶ Integration with GPIO bi-directional communication
- Special paper sizes like A6, KLT (74 x 210 mm)
- Printing with different emulations (PCL5, IGP, IPDS, etc.)





Print Engine

Power supply

Print technology Laser, OPC

heat / pressure

MPC 7.1 Controller

up to 52 pages/minute (A4) **Print speed**

first page: approx. 5.9 s

max. 600 dpi x 600 dpi Print resolution **Duty cycle** up to 50,000 pages (A4)

(based on a using period of 60 months)

max. 250,000 pages (A4) 220-240 VAC, 50/60 Hz

Power consumption 700 W (Sleep Mode: 4,2 W)

Dimensions (WxDxH) 16.9" (428 mm) x 20.1" (511 mm) x 17.4" (442 mm)

Weight 57.3 lbs (26 kg) (incl. consumables)

Noise < 57 dB (A) 10 - 32°C **Environment temperature**

Relative humidity 8 - 80 % (rel., non condensing)

Interfaces USB, Ethernet-Interface, 10/100 MBit, bi-directional (TCP/IP)

Factory Option IEEE 1284 (Centronics)

Option RS232, RS422

WIFI: IEEE 802.11 n/g/b, WEP with 64 and 128 Bit,

WPA/WPA2, WPA-PSK/WPA2-PSK

Memory RAM: 1024MB

Flash: 32 GB



MPC 7.1 High-End Print-Controller

Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, μ-Postscript, LN03+, BULL-MP6090, Datamax, Etimark MP-1220, TEC Bx72, TEC B6xx, LDC, ZPLII, EPL 2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, HP Designjet, XML (SAP® RFID), CUPS Raster, RFM

Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL, Labelpoint, IPDS, AEA, PDF Direct Printing*, (more emulations on request)

Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5, (more barcodes on request)

Additional functions

Network capabilities authentication standard IEEE 802.1X

Intelligent barcode generation on-the-fly in the printer

Format splitting in several subformats by command

Integrated form management (RFM) Forms and fonts can be stored in the flash memory

and can be accessed when needed

Optional functions

Status-Out

Gives notice of each correctly printed page via interface. Further features can be found in the manual.

Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE - Enabling two-way communication between printer and a PLC. Integration of the printer into production lines is possible, controlled by GPIO-interface

Customer / Application specific modifications possible. Further features can be found in the manual.



The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 12.07.2022

MICROPLEX PRINTWARE AG

Panzerstraße 5, 26316 Varel

Germany Phone: +49 4451 91370 E-Mail: sales@microplex.de

MICROPLEX PRINTWARE CORPORATION

30300 Solon Industrial Pkwy Suite E, Solon, OH 44139

Phone: +1 440-374-2424 E-Mail: info@microplex-usa.com

Printable Media

Size A6 to A4, special formats on request

Weight 60 - 203 g/m²

SPECIFICATIONS

Duplex 60 - 203 g/m²

Paper Path

Input (Standard)

Cassette 1: 550 sheets (Ax to A4) 75 g/m²

Output (Standard)

550 sheets (75 g/m²)

Input (optional)

550 sheets (75 g/m²) tray 550 sheets (75 g/m²) lockable tray

up to 4 x 550 sheet trays usable

or 3 x 550 sheet trays plus $1 \times 2,100$ sheet tray (75 g/m²) Caster Base for 2,100 sheet tray needed

Output (optional)

Output expander 500 sheets (75 g/m²) Face-up-Option

Other options

(non fuctioning input tray to elevate the Spacer

printer

Caster Base (only necessary for 2,100 sheet tray)

SOLID 52A4 MICR as extra model available.