



# SOLID 52A4 MICR

**TOP PERFORMANCE  
MEETS  
HIGHEST SECURITY  
STANDARDS**

## Highest Security Standards and Printing Performance

### HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Cheque printing with MICR toner for highest security standards
- Optional WIFI and PDF direct print
- Duplex printing standard
- SAP® and AS/400 compatible (through PCL5 + JetCAPS as well as LAN-IPDS)
- Flexible extension options for paper feed and tray
- Perfect control via GPIO / Status-Out

### FIELD OF APPLICATION

- Security relevant documents / cheque printing
- Paper exit face-up and face-down
- Printing with different emulations (PCL5, IPDS, etc.)
- Perfect substitution for matrix printer



## Print Engine

<b>Print technology</b>	Laser, OPC heat / pressure
<b>Controller</b>	MPC 7.1
<b>Print speed</b>	up to 52 pages/minute (A4) first page: approx. 5.9 s
<b>Print resolution</b>	max. 600 dpi x 600 dpi
<b>Duty cycle</b>	up to 50,000 pages (A4) (based on a using period of 60 months) max. 250,000 pages (A4)
<b>Power supply</b>	220-240 VAC, 50/60 Hz
<b>Power consumption</b>	700 W (Sleep Mode: 4,2 W)
<b>Dimensions (WxDxH)</b>	16.9" (428 mm) x 20.1" (511 mm) x 17.4" (442 mm)
<b>Weight</b>	57.3 lbs (26 kg) (incl. consumables)
<b>Noise</b>	< 57 dB (A)
<b>Environment temperature</b>	10 - 32°C
<b>Relative humidity</b>	8 - 80 % (rel., non condensing)
<b>Interfaces</b>	USB, Ethernet-Interface, 10/100 MBit, bi-directional (TCP/IP)
<b>Factory Option</b>	IEEE 1284 (Centronics)
<b>Option</b>	RS232, RS422 WIFI: IEEE 802.11 n/g/b, WEP with 64 and 128 Bit, WPA/WPA2, WPA-PSK/WPA2-PSK
<b>Memory</b>	RAM: 1024MB Flash: 32 GB

## MPC 7.1 High-End Print-Controller

### Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, µ-Postscript, LN03+, BULL-MP6090, Datamax, Etimark MP-1220, TEC Bx72, TEC B6xx, LDC, ZPLII, EPL 2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, HP Designjet, XML (SAP® RFID), CUPS Raster

### Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL, Labelpoint, IPDS, AEA, PDF Direct Printing\*, (more emulations on request)

### Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

### Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5, (more barcodes on request)

### Additional functions

<b>Network capabilities</b>	authentication standard IEEE 802.1X
<b>Intelligent barcode generation</b>	on-the-fly in the printer
<b>Format splitting</b>	in several subformats by command
<b>Integrated form management (RFM)</b>	Forms and fonts can be stored in the flash memory and can be accessed when needed

### Optional functions

#### Status-Out

Gives notice of each correctly printed page via interface. Further features can be found in the manual.

#### Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC.

Integration of the printer into production lines is possible, controlled by GPIO-interface

Customer / Application specific modifications possible. Further features can be found in the manual.



## Printable Media

<b>Size</b>	A6 to A4, special formats on request
<b>Weight</b>	60 - 203 g/m <sup>2</sup> Duplex 60 - 203 g/m <sup>2</sup>

### Supported MICR fonts

MICR E-13B, MICR CMC-7

## Paper Path

### Input (Standard)

Cassette 1: 550 sheets (A<sub>x</sub> to A4) 75 g/m<sup>2</sup>

### Output (Standard)

550 sheets (75 g/m<sup>2</sup>)

### Input (optional)

550 sheets (75 g/m<sup>2</sup>) tray  
550 sheets (75 g/m<sup>2</sup>) lockable tray

up to 4 x 550 sheet trays usable

### or 3 x 550 sheet trays

plus 1 x 2,100 sheet tray (75 g/m<sup>2</sup>)  
Caster Base for 2,100 sheet tray needed

### Output (optional)

Output expander 500 sheets (75 g/m<sup>2</sup>) (up to 3 times)  
Face-up-Option

### Other options

Spacer (non functioning input tray to elevate the printer)

Caster Base (only necessary for 2,100 sheet tray)

\* Only available with MPC 3.4, MPC 7.1 and MPC 8.x

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 12.07.2022

EMEA  
APAC

**MICROPLEX PRINTWARE AG**  
Panzerstraße 5, 26316 Varel  
Germany  
Phone: +49 4451 91370  
E-Mail: sales@microplex.de

AMER  
Canada

**MICROPLEX PRINTWARE CORPORATION**  
30300 Solon Industrial Pkwy Suite E, Solon, OH 44139  
USA  
Phone: +1 440-374-2424  
E-Mail: info@microplex-usa.com



PRINTING TECHNOLOGIES  
ENGINEERED IN GERMANY

www.microplex-usa.com