

SOLID F90HD

HIGH PERFORMANCE,
IMPRESSIVE COST
EFFECTIVENESS

Efficient Flash Fusing Printer for Sensitive Materials

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Prints on paper, PVC, plastic, etc.
- USB, Ethernet (10/100/1000 Mbit) as standard
- > Laser and matrix printer compatible
- SAP® and AS/400 compatible (through PCL5 + JetCAPS as well as LAN-IPDS)
- Perfect control via Status Out

FIELD OF APPLICATION

- > Label batch printing
- Ticket printing
- Business and logistics documents



SOLID F90HD

Print Engine

Print technology LED, OPC, xenon flash lamp with halogen preheat

MPC 3.4 Controller **Print speed** 3.000 lpm (6 lpi) 12.7 m/min

up to 85 pages/minute (A4 2-up)

Print resolution max. 600 dpi x 600 dpi **Duty cycle** up to 750.000 pages (A4 2-up)

(based on a using period of 60 month)

Power supply 230 VAC +/-10%, 50 Hz (delivery with 32 Amp. connector)

max. 5.5 KVA (in operation) Power consumption

max. 0.6 KVA (in stand-by)

30.7" (780 mm) x 35" (890 mm) x 51.9" (1320 mm) (Printer only) Dimensions (WxDxH)

30.7" (780 mm) x 36.8" (935 mm) x 51.9" (1320 mm) (Printer w. Stacker)

Weight 606.3 lbs (275 kg) (with Stacker)

Environment temperature 15 - 30°C

Relative humidity 30 - 80 % (rel., non-condensing)

Interfaces USB

Ethernet-Interface 10/100/1000 MBit, bi-direktional (TCP/IP)

Optional IEEE 1284 (Centronics).

WIFI IEEE 802.11 n/g/b,

WEP mit 64 und 128 Bit, WPA/WPA2, WPA-PSK/WPA2-PSK

Memory RAM: 4 GB

Flash: 16 GB

MPC 3.4 High-End Print-Controller

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, µ-Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, XML (SAP® RFID), CUPS Raster

Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL, Datamax, Labelpoint, LDC, ZPLII, EPL 2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, HP Designjet, IPDS, AEA, PDF Direktdruck*, (more emulations on request)

Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Additional functions

Network compatibility authentication standard IEEE 802.1X

Intelligent barcode generation on-the-fly in the printer

Format splitting in several subformats by command

Integrated form management Forms and fonts can be stored in the flash memory (RFM)

and can be accessed when needed

Optional functions

Status-Out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE - Enabling two-way communication between printer and a PLC. Integration of the printer into production lines is possible, controlled by GPIO-interface Customer / Application specific modifications possible.



The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 12.07.2022

MICROPLEX PRINTWARE AG

Panzerstraße 5, 26316 Varel

Phone: +49 4451 91370 E-Mail: sales@microplex.de

MICROPLEX PRINTWARE CORPORATION

30300 Solon Industrial Pkwy Suite E, Solon, OH 44139

Phone: +1 440-374-2424 E-Mail: info@microplex-usa.com






SPECIFICATIONS

Printable Media

Size

Form length 7" - 24" 7" - 14" With stacker Form width 6" - 18" Printable area 17"

Weight 60 - 204 g/m²



Paper Path

Input

push tractor

Output

stacker

capacity: 3,000 pages (at 64 g/m²)