



# LogiJET T4-2

**MAXIMUM FLEXIBILITY  
FOR SMOOTH  
PRODUCTION  
AND LOGISTICS  
PROCESSES**

## PCL5 Compatible 4 Inch Thermal Printer

### HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Compatible with: PCL5, IGP, IPDS, PDF, ZPL II, and many more.
- WIFI optional
- Laser printer compatible
- SAP® and AS/400 compatible (through PCL5 + JetCAPS as well as LAN-IPDS)
- Process integration with optional GPIO interface
- RFID optional

### FIELDS OF APPLICATION

- Stickers, labels and tags
- RFID tags
- Just-in-time printing or batch processing
- Logistics, commissioning, production, shipping, etc.



## Print Engine

<b>Print technology</b>	Thermal transfer/direct thermal harmonic (history-controlled flat head technology)
<b>Controller</b>	MPC 8.x
<b>Print speed</b>	up to 6 Inch/s up to 150 mm/s
<b>Print resolution</b>	300 dpi x 300 dpi
<b>Lifetime print head</b>	Transfer: up to 50.000 m, Direct: up to 25.000 m
<b>Power supply</b>	110/240VAC, 50/60Hz
<b>Power consumption</b>	2,5 A
<b>Dimensions (WxDxH)</b>	10.8" [275 mm] x 20.7" [525 mm] x 11.4" [290 mm]
<b>Weight</b>	33.1 lbs [15 kg] (without options)
<b>Environment temperature</b>	5 - 40°C
<b>Relative humidity</b>	30 - 85 % (rel., non-condensing)
<b>Interfaces</b>	USB 2.0 Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP)
<b>Optional*</b>	IEEE 1284 (Centronics), RS232, RS422 WiFi: IEEE 802.11 n/g/b, WEP with 64 and 128 Bit, WPA/WPA2, WPA-PSK/WPA2-PSK
<b>Memory</b>	RAM 256 MB Flash 256 MB

## MPC 8.x High-End Print-Controller

### Emulations

MICROPLEX IDOL, AGFA Reno, LN03+, BULL-MP6090, IGP/PGL, Datamax, Etimark MP-1220, TEC Bx72, TEC B6xx, LDC, ZPL II, EPL2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, Diablo 630, IBM Proprinter, Epson FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, HP Designjet, XML (SAP® RFID), CUPS Raster

### Optional Emulations

HP-PCL5/ HPGL, µ-Postscript, CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, Labelpoint, IPDS, AEA, PDF Direct Printing\*\* (more emulations on request)

### Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

### Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5  
(more barcodes on request)

### Additional functions

<b>Network capabilities</b>	authentication standard IEEE 802.1X
<b>Intelligent barcode generation</b>	on-the-fly in the printer
<b>Format splitting</b>	in several subformats by command

### Optional functions

#### Integrated form management (RFM)

Forms and fonts can be stored in the flash memory and can be accessed when needed.

#### Status-Out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

#### Programmable GPIO-Interface (SPS-Control)


EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC.

Integration of the printer into production lines is possible, controlled by GPIO-interface Customer / Application specific modifications possible.



## Printable Media

<b>Size</b>	
Width	max. 4.65" [118 mm] printable width 4.1" [106 mm]
roll diameter	max. 8" [203 mm] with 3" core
core diameter	1.5" - 3" [38.1 - 76.2 mm]
<b>Paper thickness</b>	0.0024" - 0.01" [0.06 - 0.25 mm]
<b>Thermal transfer ribbon</b>	Roll diameter max. 3" [78 mm]
<b>Core diameter</b>	1" [25.4 mm]
<b>Ribbon length</b>	max. 450 m
<b>Coated side</b>	inside or outside
<b>Ribbon width</b>	1.18" - 4.33" [30 - 110 mm]



## Paper Path

### Input

continuous  
internal from roll, external (e.g. fanfold), sensor for black mark and label gap (reflection and transmissive)

### Output

<b>Single/Job</b>	tear-off
<b>Optional</b>	
Continuous	internal peeler / rewriter
Single	peel-off, cutter
Job	cutter

### Option RFID

#### Frequency Range

865.600 - 867.600 MHz (ETSI EN 302 208)

#### RF Power

programmable in 15 levels (1 dB step) from 9 dBm to 23 dBm  
(from 8 mW to 200 mW) conducted

**Standard Protocols** EPC C1 G2 / ISO18000-6C

**Features** read/write/verify (void)

#### Registration of antenna position

automatic (depending on antenna design)

\* Not all interface options can be activated at the same time.  
\*\* Only available with MPC 3.4, MPC 3.6, MPC 7.1 and MPC 8.x

EMEA  
APAC

**MICROPLEX PRINTWARE AG**  
Panzerstraße 5, 26316 Varel  
Germany  
Phone: +49 4451 91370  
E-Mail: sales@microplex.de

AMER  
Canada

**MICROPLEX PRINTWARE CORPORATION**  
30300 Solon Industrial Pkwy Suite E, Solon, OH 44139  
USA  
Phone: +1 440-374-2424  
E-Mail: info@microplex-usa.com

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 12.07.2022

