



# A3 laser Printer for Just-in-Time Applications

# HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Breakneck 3 seconds to printing of first page
- Duplex printing at full speed (up to 26 pages (A4)/minute)
- > Flexible extension options for paper feed and tray
- Full integration in production lines through SPS control and Status-Out

# FIELD OF APPLICATION

- Just-in-time applications
- On-demand printing
- Business and workflow documents
- **>** ecommerce



### **SOLID 50A3-3**



#### **Print Engine**

Print technology Laser, OPC

heat / pressure

Controller MPC 5.2 with Intel XScale PXA 255

(400-MHz-RISC-Processor)

**Print speed** up to 50 pages/minute (A4)

first page: < 3 s

 Print resolution
 max. 600 dpi x 600 dpi

 Duty cycle
 up to 50.000 pages [A4]

(based on a using period of 60 months)

max. 250,000 pages (A4)

**Power supply** 220-240 VAC, 50/60 Hz

Power consumption 8 A

**Dimensions (WxDxH)** 25.2" [640 mm] x 22" (559 mm) x 19" (483 mm)

Weight 105.8 lbs (48 kg) (incl. consumables)

Environment temperature 10 - 32°C

**Relative humidity** 20 - 80 % (rel., non condensing)

Interfaces USB, RS232, RS422

IEEE 1284 (Centronics)

Ethernet-Interface, 10/100 MBit, bi-directional (TCP/IP)

**Memory** RAM: 128MB

Flash: 16MB

### MPC 5.2 High-End Print-Controller



# Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno,  $\mu$ -Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, XML (SAP® RFID), CUPS Raster

#### **Optional Emulations**

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL. cab, Datamax, Datamax, Labelpoint, LDC, ZPL II, EPL 2, Intermec Direct Protocol, IER Command, Godex EZPL, HP Designjet, IPDS, AEA, [more emulations on request]

#### Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

#### Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

#### Additional functions

Intelligent barcode generation on-the-fly in the printer

Format splitting in several subformats by command

Integrated form management (RFM) Forms and fonts can be stored in the flash memory

and can be accessed when needed

#### **Optional functions**

#### Status-Out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

#### Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC. Integration of the printer into production lines is possible, controlled by GPIO-interface Customer / Application specific modifications possible.


## **SPECIFICATIONS**



#### Printable Media

 Size
 A5 bis A3

 Weight
 64-163 g/m² Duplex 60-120 g/m²



#### **Paper Path**

#### Input

cassette 1: 500 sheets (A5 to A3) cassette 2: 500 sheets (A5R\* to A3) manual input: 100 sheets (A5 to A3)

#### **Optional**

cassette 3+4: 500 sheets (A5R\* to A3) 2,000 sheets feeder (A4, Letter)

#### Output

500 sheets, face down duplex unit

#### Optional

100 sheets, face up

\*A5R = A5 short side feeding

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 12.07.2022

EMEA

MICROPLEX PRINTWARE AG

Panzerstraße 5, 26316 Varel

Germany

Phone: +49 4451 91370 E-Mail: sales@microplex.de AMER Canada MICROPLEX PRINTWARE CORPORATION

30300 Solon Industrial Pkwy Suite E, Solon, OH 44139

Phone: +1 440-374-2424 E-Mail: info@microplex-usa.com

